



The Department of Veterans Affairs
Federal Supply Service
Authorized Federal Supply Schedule Price List
Update 8-1-16

On-line access to contract ordering information, terms and conditions, up-to-date pricing, and the option to create an electronic delivery order are available through GSA Advantage!, a menu-driven database system. The INTERNET address for GSA Advantage is: GSAAdvantage.gov.

Medical Equipment and Supplies
FSC Group 65, Part II, Section A
FSC Class: 70
Contract Number: V797D-30207

For more information on ordering Federal Supply Schedules click on the FSS Schedules button at fss.gsa.gov.

Contract Period: July 1, 2013 –June 30, 2018

Contractor Name Aldevra
 Address 251 N. Rose St., Suite 200, Kalamazoo, MI 49007
 Phone # 269-350-1337
 Fax # 269-327-7392

Contract Administration Source Maggie Bullard-Marshall

Business Size Service Disabled Veteran Owned Small Business; Historically Underutilized Business Zone (HUBZone); 8(a) Small Disadvantaged Business

Tax Identification Number (TIN) 264111029

CUSTOMER INFORMATION:

1a. Table of awarded special item number(s) with appropriate cross-reference to item descriptions and awarded price(s).

SIN	Item #	Product Name / Description	FSS Price
A-70	00105072	extra key	22.72
A-70	00112185	temperature alarm	321.27
A-70	00114702	Pyxis compatible door bracket	123.13
A-70	00131748	epoxy-coated cut-away shelf (fits around drain line)	74.43
A-70	00153700	wall mount bracket	259.32

A-70	00158014	Omicell compatible door bracket	55.84
A-70	00159699	shelf	78.16
A-70	00162081	replacement pens (box of 6)	64.14
A-70	00162099	replacement charts	66.89
A-70	00168674	temperature surveillance	952.35
A-70	00905646	temperature probe	164.80
A-70	00918813	replacement pens, red (set of 6)	\$63.48

A-70	00918821	6" chart paper (box of 50)	\$83.79
A-70	00926618	stacking kit	\$289.07
A-70	00927202	Pyxis compatible door bracket	150.47
A-70	00927251	additional shelves (2) for REF20	131.44
A-70	00927269	additional shelves (2) for REF25	132.74
A-70	00931154	pedestal base (ordered with equipment), 23.75" wide x 24" deep x 17" high (604 x 610 x 432 mm), stainless	\$584.50
A-70	00939785	replacement Crs (Complete refrigeration system) module	1563.63

A-70	00945436	extra key	\$35.46
A-70	00959296	Glycerol solution, 16 oz.	39.62
A-70	00966432	Omicell compatible door bracket	168.84
A-70	00967729	6" chart paper (box of 50)	\$87.81
A-70	00969931	bin, organizing (set of 6)	47.17
A-70	00969949	wall mount kit	281.34
A-70	00969956	additional shelf	48.07

A-70	00978262	MedDispense compatible door bracket	\$59.81
A-70	00978296	MedDispense compatible door bracket	172.47
A-70	01025881	pedestal, 12" (304.8 mm)	261.94
A-70	01025899	pedestal, fan-assist, 4.5" (114.3 mm)	213.88
A-70	01035013	Extra key	\$35.55
A-70	01053636	Casters for undercounter REFs and FZR - set of 4	133.24
A-70	01054006	Stacking kit (Performance Plus on Performance Plus)	293.87

A-70	01057561	touchscreen digital data logger accessory kit for continuous temperature monitoring at programmable intervals	829.62
A-70	01059096	Universal ADC-compatible bracket (for all medication dispensing system locks)	68.27
A-70	01059112	Extra key for Performance Plus	22.75
A-70	01059484	Extra shelf (1) - REF4P/T, 5P/T, 5BB-T, FZR4P/T, 5P/T, 5PLP-T	83.99
A-70	01067172	stacking kit for legacy model undercounter REF or FZR to be stacked on top of Performance Plus REF or FZR	288.64
A-70	chart recorder	chart recorder	\$769.37
A-70	FZR1	Freezer with solid stainless steel door fits on standard 24.00" (61.0 cm) deep countertop and under 18.00" (45.7 cm) wall hung cabinets with 0.6 cubic feet (16 L) of nominal capacity. Includes (1) epoxy-coated wire shelf. Environmentally responsible R404a forced-air cooled refrigeration system. Bottom-mounted controls display product temperature in user selectable C or F. Integral high and low temperature alarming. Storage area insulated with CFC-free high-density polyurethane foam. 8' (2.4 m) power cord with NEMA 5-15p 90 degree hospital-grade plug. NSF, UL and cUL listed.	2639.05

A-70	FZR1-KP	Freezer with solid stainless steel door fits on standard 24.00" (61.0 cm) deep countertop and under 18.00" (45.7 cm) wall hung cabinets with 0.6 cubic feet (16 L) of nominal capacity. Includes (1) epoxy-coated wire shelf. Environmentally responsible R404a forced-air cooled refrigeration system. Bottom-mounted controls display product temperature in user selectable C or F. Integral high and low temperature alarming. Storage area insulated with CFC-free high-density polyurethane foam. 8' (2.4 m) power cord with NEMA 5-15p 90 degree hospital-grade plug. NSF, UL and cUL listed. Includes keypad	2958.97
A-70	FZR2	Freezer with solid stainless steel door fits on standard 24.00" (61.0 cm) deep countertop with 1.6 cubic feet (44 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in ½" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Bottom-mounted controls display product temperature in user selectable C or F. Integral high and low temperature alarming. Storage area insulated with CFC-free high-density polyurethane foam. 8' (2.4 m) power cord with NEMA 5-15p 90 degree hospital-grade plug. NSF, UL and cUL listed.	2792.61
A-70	FZR20-LB	FZR20-LB single door lab freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 30.5"d X 79.5"h	6714.7
A-70	FZR20-LB-LHT00	FZR20-LB-LHT00 single door lab freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 30.5"d X 79.5"h Left Hinge; Heated Door	6361.53
A-70	FZR20-LB-LHTCR	FZR20-LB-LHTCR single door lab freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 30.5"d X 79.5"h Left Hinge; Heated Door; with Chart Recorder	7165.07
A-70	FZR20-LB-RHT00	FZR20-LB-RHT00 single door lab freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 30.5"d X 79.5"h; Right Hinge; Heated Door	6361.53

A-70	FZR20-LB-RHTCR	FZR20-LB_RHTCR single door lab freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 30.5"d X 79.5"h Right Hinge; Heated Door; with Chart Recorder	7165.07
A-70	FZR20-PL	FZR20-PL single door plasma freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 8 full extension SS drawers; store up to 352-300ml plasma cardboard packs; 29.75"w X 30.5"d X 79.5"h	10046.41
A-70	FZR20-PL-LHTCR	FZR20-PL-LHTCR single door plasma freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 8 full extension SS drawers; store up to 352-300ml plasma cardboard packs; 29.75"w X 30.5"d X 79.5"h; Left Hinged; Heated Door; with Chart Recorder	10058.79
A-70	FZR20-PL-RHTCR	FZR20-PL-RHTCR single door plasma freezer; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 8 full extension SS drawers; store up to 35;2-300ml plasma cardboard packs; 29.75"w X 30.5"d X 79.5"h; Right Hinged; Heated Door; with Chart Recorder	10058.79
A-70	FZR25-LB	FZR25-LB single door lab freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 36.5"d X 79.5"h	7096.83
A-70	FZR25-LB-LHT00	FZR25-LB-LHT00 single door lab freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 36.5"d X 79.5"h; Left Hinge; Heated Door	6887.80

A-70	FZR25-LB-LHTCR	FZR25-LB-LHTCR single door lab freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 36.5"d X 79.5"h; Left Hinge; Heated Door; with Chart Recorder	7691.14
A-70	FZR25-LB-RHT00	FZR25-LB-RHT00 single door lab freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 36.5"d X 79.5"h; Right Hinge; Heated Door	6887.80
A-70	FZR25-LB-RHTCR	FZR25-LB-RHTCR single door lab freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy coated shelves; 29.75"w X 36.5"d X 79.5"h; Right Hinge; Heated Door; with Chart Recorder	7691.14
A-70	FZR25-PL	FZR25-PL single door plasma freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 8 full extension SS drawers; store up to 352-300ml plasma cardboard packs; 29.75"w X 36.5"d X 79.5"h	10614.60
A-70	FZR25-PL-LHTCR	FZR25-PL-LHTCR single door plasma freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 8 full extension SS drawers; store up to 352-300ml plasma cardboard packs; 29.75"w X 36.5"d X 79.5"h; Left Hinged; Heated Door; with Chart Recorder	10624.07
A-70	FZR25-PL-RHTCR	FZR25-PL-RHTCR single door plasma freezer; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 8 full extension SS drawers; store up to 352-300ml plasma cardboard packs; 29.75"w X 36.5"d X 79.5"h; Right Hinged; Heated Door; with Chart Recorder	10624.07

A-70	FZR2-KP	Freezer with solid stainless steel door fits on standard 24.00" (61.0 cm) deep countertop with 1.6 cubic feet (44 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in ½" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Bottom-mounted controls display product temperature in user selectable C or F. Integral high and low temperature alarming. Storage area insulated with CFC-free high-density polyurethane foam. 8' (2.4 m) power cord with NEMA 5-15p 90 degree hospital-grade plug. NSF, UL and cUL listed. Includes keypad	3112.54
A-70	FZR4P	Performance Plus series undercounter freezer fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	3438.42
A-70	FZR4P-00-00	FZR4P-00-00 Performance Plus series undercounter freezer fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes(2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with .NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed	3447.33
A-70	FZR4P-KP-00	FZR4P-KP-00 Performance Plus series undercounter freezer fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes(2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with .NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed; with Keypad	3779.86

A-70	FZR4P-T	Performance Plus series undercounter freezer fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. 7" LCD touchscreen display. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	4052.25
A-70	FZR4P-T-00-00	FZR4P-T-00-00 Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	4061.19
A-70	FZR4P-T-KP-00	FZR40-T-KP-00 Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed; with Keypad	4245.27
A-70	FZR5P	Performance Plus series undercounter freezer fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and	3446.65

		CUL listed.	
A-70	FZR5P-00-00	FZR5P-00-00 Performance Plus series undercounter freezer fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	3447.33
A-70	FZR5P-KP-00	FZR5P-KP-00 Performance Plus series undercounter freezer fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed. With Keypad.	3779.86
A-70	FZR5PLP-T	Performance Plus series plasma freezer for freestanding or undercounter use, fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (40) 300 ml plasma packs. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7" (2.1 m) power cord with NEMA 5-15P 90 degree hospital-grade plug. NSF, UL and CUL listed.	5433.72

A-70	FZR5PLP-T-00-00	FZR5PLP-T-00-00 Performance Plus plasma freezer for freestanding or undercounter use, fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (40) 300 ml plasma packs. Environmentally responsible R404a forcedair cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	5422.03
A-70	FZR5PLP-T-KP-00	FZR5PLP-T-KP-00 Performance Plus plasma freezer for freestanding or undercounter use, fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (40) 300 ml plasma packs. Environmentally responsible R404a forcedair cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.With Touchscreen Keypad	5606.11
A-70	FZR5P-T	Performance Plus series undercounter freezer fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. 7" LCD touchscreen display. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	4060.51
A-70	FZR5P-T-00-00	FZR5P-T-00-00 Performance Plus undercounter freezer fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be	4061.19

		insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital lgrade plug. NSF, UL and CUL listed.	
A-70	FZR5P-T-KP-00	FZR5P-T-KP-00 Performance Plus undercounter freezer fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital lgrade plug. NSF, UL and CUL listed. With Keypad	4245.27
A-70	heated door	heated door	\$185.97
A-70	KEYPAD4	Factory-installed keypad locking system, REF4 ADA	\$328.64
A-70	KEYPAD5	Factory-installed keypad locking system, REF5	\$328.64
A-70	left hinged door	left hinged door	\$185.97

A-70	REF1	Medical grade countertop refrigerator with powerful forced-air cooling S/S exterior and interior 1.0 cu ft; Heavy-duty compressor and forced-air cooling provide superior temperature pull-down and immediate recovery; Quiet compressor and coaxial fans allow use in noise-sensitive areas; Exterior LED displays product temperature in user-selectable F or C ; Audible and visual high and low alarms and keylock provide product security; Compatible with all automated medication dispensing systems; Stainless steel interior and exterior, heavy-duty components and automatic defrost provide exceptional durability and convenience;115V, 60 Hz, 1 phase, 1.8A, maximum fuse 15A;18.6"w X 24"d X 17.75"h;95 lbs. shipping weight	1808.25
A-70	REF2	Medical grade countertop refrigerator with powerful forced-air cooling S/S exterior and interior 1.8 cu ft; Heavy-duty compressor and forced-air cooling provide superior temperature pull-down and immediate recovery; Quiet compressor and coaxial fans allow use in noise-sensitive areas; Exterior LED displays product temperature in user-selectable F or C; Audible and visual high and low alarms and keylock provide product security;Compatible with all automated medication dispensing systems; Stainless steel interior and exterior, heavy-duty components and automatic defrost provide exceptional durability and convenience; 115V, 60 Hz, 1 phase, 1.8A, maximum fuse 15A; 18.6"w X 10"d X 21.25"h;109 lbs. shipping weight	1917.70
A-70	REF20-BB	REF20-BB single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 30.5"d X 79.5"h	7054.11
A-70	REF20-BB-L00CR	REF20-BB-L00CR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 30.5"d X 79.5"h; Left Hinged; with Chart Recorder	7097.60

A-70	REF20-BB-LHTCR	REF20-BB-LHTCR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 30.5"d X 79.5"h; Left Hinged; Heated Door; with Chart Recorder	7289.47
A-70	REF20-BB-R00CR	REF20-BB-R00CR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 30.5"d X 79.5"h; Right Hinged; with Chart Recorder	7097.60
A-70	REF20-BB-RHTCR	REF20-BB-RHTCR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 30.5"d X 79.5"h; Right Hinged; Heated Door; with Chart Recorder	7289.47
A-70	REF20-LB	REF20-LB single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h	4810.69
A-70	REF20-LB-L0000	REF20-LB-L0000 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h Left Hinged	4824.19
A-70	REF20-LB-L00CR	REF20-LB-L00CR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h Left Hinged; with Chart Recorder	5627.51

A-70	REF20-LB-LHT00	REF20-LB-LHT00 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h Left Hinged; Heated Door	5016.03
A-70	REF20-LB-LHTCR	REF20-LB-LHTCR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h Left Hinged; Heated Door; with Chart Recorder	5819.36
A-70	REF20-LB-R0000	REF20-LB-R0000 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h; Right Hinged	4824.19
A-70	REF20-LB-R00CR	REF20-LB-R00CR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h; Right Hinged; with Chart Recorder	5627.51
A-70	REF20-LB-RHT00	REF20-LB-RHT00 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h; Right Hinged; Heated Door	5016.03
A-70	REF20-LB-RHTCR	REF20-LB-RHTCR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 30.5"d X 79.5"h; Right Hinged; Heated Door; with Chart Recorder	5819.36
A-70	REF20-PH	REF20-PH single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h	5121.44

A-70	REF20-PH-L0000	REF20-PH-L0000 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Left Hinged	5357.82
A-70	REF20-PH-L00CR	REF20-PH-L00CR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Left Hinged; with Chart Recorder	6161.17
A-70	REF20-PH-LHT00	REF20-PH-LHT00 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Left Hinged; Heated Door	5549.67
A-70	REF20-PH-LHTCR	REF20-PH-LHTCR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Left Hinged; Heated Door; with Chart Recorder	6353.03
A-70	REF20-PH-R0000	REF20-PH-R0000 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Right Hinged	5357.82
A-70	REF20-PH-R00CR	REF20-PH-R00CR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Right Hinged; with Chart Recorder	6161.17
A-70	REF20-PH-RHT00	REF20-PH-RHT00 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Right Hinged; Heated Door	5549.67

A-70	REF20-PH-RHTCR	REF20-PH-RHTCR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 19.7 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 30.5"d X 79.5"h; Right Hinged; Heated Door; with Chart Recorder	6353.03
A-70	REF25-BB	REF25-BB single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 36.5"d X 79.5"h	9402.41
A-70	REF25-BB-L00CR	REF25-BB-L00CR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 36.5"d X 79.5"h; Left Hinged; with Chart Recorder	7583.99
A-70	REF25-BB-LHTCR	REF25-BB-LHTCR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 36.5"d X 79.5"h; Left Hinged; Heated Door; with Chart Recorder	7775.86
A-70	REF25-BB-R00CR	REF25-BB-R00CR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 36.5"d X 79.5"h; Right Hinged; with Chart Recorder	7583.99
A-70	REF25-BB-RHTCR	REF25-BB-RHTCR single door blood bank refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 full extension "floating" SS drawers;29.75"w X 36.5"d X 79.5"h; Right Hinged; Heated Door; with Chart Recorder	7775.86

A-70	REF25-LB	REF25-LB single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h	5152.86
A-70	REF25-LB-L0000	REF25-LB-L0000 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Left Hinged	5182.52
A-70	REF25-LB-L00CR	REF25-LB-L00CR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Left Hinged; with Chart Recorder	5985.87
A-70	REF25-LB-LHT00	REF25-LB-LHT00 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Left Hinged; Heated Door	5374.37
A-70	REF25-LB-LHTCR	REF25-LB-LHTCR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Left Hinged; Heated Door; with Chart Recorder	6177.73
A-70	REF25-LB-R0000	REF25-LB-R0000 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Right Hinged	5182.52
A-70	REF25-LB-R00CR	REF25-LB-R00CR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Right Hinged; with Chart Recorder	5985.87

A-70	REF25-LB-RHT00	REF25-LB-RHT00 single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Right Hinged; Heated Door	5374.37
A-70	REF25-LB-RHTCR	REF25-LB-RHTCR single door lab refrigerator.; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane; locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 4 epoxy-coated adjustable shelves;29.75"w X 36.5"d X 79.5"h; Right Hinged; Heated Door; with Chart Recorder	6177.73
A-70	REF25-PH	REF25-PH single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h	5368.04
A-70	REF25-PH-L0000	REF25-PH-L0000 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h; Left Hinged	5670
A-70	REF25-PH-L00CR	REF25-PH-L00CR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h; Left Hinged; with Chart Recorder	6473.33
A-70	REF25-PH-LHT00	REF25-PH-LHT00 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h; Left Hinged; Heated Door	5861.85
A-70	REF25-PH-LHTCR	REF25-PH-LHTCR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h; Left Hinged; Heated Door; with Chart Recorder	6665.43

A-70	REF25-PH-R0000	REF25-PH-R0000 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h;Right Hinged	5670.00
A-70	REF25-PH-R00CR	REF25-PH-R00CR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h;Right Hinged; with Chart Recorder	6473.33
A-70	REF25-PH-RHT00	REF25-PH-RHT00 single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h;Right Hinged; Heated Door	5861.85
A-70	REF25-PH-RHTCR	REF25-PH-RHTCR single door pharmacy refrigerator; Stainless steel interior/exterior; Capacity 24.6 cu ft; Dual-pane locking door with right hand hinges; Digital LED temperature display; top temperature probe; User-programmable alarming and monitoring functions; 6 epoxy-coated baskets; 29.75"w X 36.4"d X 79.5"h;Right Hinged; Heated Door; with Chart Recorder	6665.43
A-70	REF4P	Performance Plus series undercounter refrigerator with solid stainless steel door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	2315.60
A-70	REF4P-00-00	Performance Plus series undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord	2316.27

		with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	
A-70	REF4P-00-GD	Performance Plus series undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed. With glass door.	2559.62
A-70	REF4P-KP-00	Performance Plus series undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed. With LED Keypad.	2649.09
A-70	REF4P-KP-GD	Performance Plus series undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed. With LED Keypad and glass door.	2892.28

A-70	REF4P-T	Performance Plus series undercounter refrigerator with solid stainless steel door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. 7" LCD touchscreen display. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	2929.95
A-70	REF4P-T-00-00	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed.	2930.63
A-70	REF4P-T-00-GD	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With glass door.	3173.70
A-70	REF4P-T-KP-00	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated	3114.86

		with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With Keypad.	
A-70	REF4P-T-KP-GD	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With Keypad and glass door.	3357.86
A-70	REF5BBP-T	Performance Plus series blood bank refrigerator for freestanding or undercounter use, with solid stainless steel door fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (50) 450 ml blood bags. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1m) power cord with NEMA 5-15P 90 degree hospital-grade plug. NSF, UL and CUL listed.	4290.24
A-70	REF5BBP-T-00-00	Performance Plus blood bank refrigerator for freestanding or undercounter use, with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (50) 450 ml blood bags. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and	4278.62

		CUL listed.	
A-70	REF5BBP-T-00-GD	Performance Plus blood bank refrigerator for freestanding or undercounter use, with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (50) 450 ml blood bags. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With glass door.	4521.71
A-70	REF5BBP-T-KP-00	Performance Plus blood bank refrigerator for freestanding or undercounter use, with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (50) 450 ml blood bags. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With Keypad.	4462.86
A-70	REF5BBP-T-KP-GD	Performance Plus blood bank refrigerator for freestanding or undercounter use, with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) full extension stainless steel drawers which store up to (50) 450 ml blood bags. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in user-selectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. 7-day analog chart recorder. Storage area to be insulated with CFC-free,	4705.89

		high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With Keypad and glass door.	
A-70	REF5P	Performance Plus series undercounter refrigerator with solid stainless steel door fits under 36.00" (91.4 cm) standard height counter height with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed	2315.60
A-70	REF5P-00-00	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter height with 4.5 cubic feet (127 L) of nominal capacity. Includes(2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.	2316.27
A-70	REF5P-00-GD	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter height with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed. With glass door.	2559.62
A-70	REF5P-KP-00	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter height with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted	2649.09

		controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed. With LED Keypad.	
A-70	REF5P-KP-GD	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter height with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed. With LED Keypad and glass door.	2892.28
A-70	REF5P-T	Performance Plus series undercounter refrigerator with solid stainless steel door fits under 36.00" (91.4 cm) standard height counter height with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. 7" LCD touchscreen display. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed	2929.95
A-70	REF5P-T-00-00	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter with 4.5 (127 L) cubic feet of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download	2930.63
A-70	REF5P-T-00-GD	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter with 4.5 (127 L) cubic feet of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB	3173.70

		download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With glass door.	
A-70	REF5P-T-KP-00	Performance Plus undercounter refrigerator with choice of solid stainless steel	3114.86
A-70	REF5P-T-KP-GD	Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter with 4.5 (12 L) cubic feet of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls with LCD touchscreen display product or air temperature in userselectable C or F. Event and data logging with USB download capability. Integral high and low temperature alarming. Storage area to be insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospitalgrade plug. NSF, UL and CUL listed. With Keypad and glass door.	3357.86
Eff. 8/1/16			
A-70	REF1-KP	Medical grade countertop refrigerator with powerful forced-air cooling S/S exterior and interior 1.0 cu ft; Heavy-duty compressor and forced-air cooling provide superior temperature pull-down and immediate recovery; Quiet compressor and coaxial fans allow use in noise-sensitive areas; Exterior LED displays product temperature in user-selectable F or C ; with Keypad; Audible and visual high and low alarms and keylock provide product security; Compatible with all automated medication dispensing systems; Stainless steel interior and exterior, heavy-duty components and automatic defrost provide exceptional durability and convenience;115V, 60 Hz, 1 phase, 1.8A, maximum fuse 15A;18.6""w X 24""d X 17.75""h;95 lbs. shipping weight	2137.49
A-70	REF2-KP	Medical grade countertop refrigerator with powerful forced-air cooling S/S exterior and interior 1.8 cu ft; Heavy-duty compressor and forced-air cooling provide superior temperature pull-down and immediate recovery; with Keypad;Quiet compressor and coaxial fans allow use in noise-sensitive areas; Exterior LED displays product temperature in user-selectable F or C;	\$2,247.54

		Audible and visual high and low alarms and keylock provide product security;Compatible with all automated medication dispensing systems; Stainless steel interior and exterior, heavy-duty components and automatic defrost provide exceptional durability and convenience; 115V, 60 Hz, 1 phase, 1.8A, maximum fuse 15A; 18.6"w X 10"d X 21.25"h;109 lbs. shipping weight	
A-70	1059120	pedestal base REF5P and REF4P	\$552.22
A-70	1100759	stacking kit for countertop on perf plus	\$283.82

- 1b. Identification of the lowest priced model number and lowest unit price for that model for each special item number awarded in the contract. This price is the Government price based on a unit of one, exclusive of any quantity/dollar volume, prompt payment, or any other concession affecting price. Those contracts that have unit prices based on the geographic location of the customer, should show the range of the lowest price, and cite the areas to which the prices apply.

See above

2. Maximum order. \$50,000, call for orders above
3. Minimum order. \$100
4. Geographic coverage (delivery area). FOB Destination to contiguous 48 states; call for others
5. Point(s) of production (city, county, and State or foreign country). Easton, PA, USA
6. Discount from list prices or statement of net price. 52.84%
7. Quantity discounts. 1.5% for qty 3 or more (same shipping location/same order); Government receives rebate for sales more than \$300,000
8. Payment terms. Net 30
- 9a. Notification that Government purchase cards are accepted up to the micro-purchase threshold. Yes
- 9b. Notification whether Government purchase cards are accepted or not accepted above the micro-purchase threshold. Yes
10. Foreign items (list items by country of origin). N/A

- 11a. Time of delivery. 30 days ARO
- 11b. Expedited Delivery. All items available for expedited delivery upon request. 7-10 days ARO. Ordering facility will pay the difference between normal and expedited shipping costs.
- 11c. Overnight and 2-day delivery. Call for rates for overnight and 2-day delivery.
- 11d. Urgent Requirements. Agencies may contact the Contractor's representative to effect a faster delivery.
- 12. F.o.b. point(s). Destination to continuous 48 states
- 13a. Ordering address(es). 251 N. Rose St., Suite 200, Kalamazoo, MI 49007 or sales@aldevra.com
- 13b. Ordering procedures: For supplies and services, the ordering procedures, information on Blanket Purchase Agreements (BPA's), and a sample BPA can be found at the GSA/FSS Schedule homepage (fss.gsa.gov/schedules).
- 14. Payment address(es). 251 N. Rose St., Suite 200, Kalamazoo, MI 49007
- 15. Warranty provision.

**Refrigerator and Freezer Warranty for GSA Schedule Purchases
USA/Canada**

Medical-grade countertop and undercounter refrigerators and undercounter freezers

Aldevra warrants via Follett Corporation to the original purchaser that all parts shall be free from defects in material and workmanship under normal use and service for a period of 2 years from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts and labor for repair within this 2 year period are covered under this warranty. The compressor shall be covered for an additional 3 years (parts only), for a total of 5 years from the date of installation.

Medical-grade upright refrigerators

Aldevra warrants via Follett Corporation to the original purchaser that all parts shall be free from defects in material and workmanship under normal use and service for a period of 2 years from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts for repair within this 2 year period are covered under this warranty. Labor required for repair within a 1 year period is covered under this warranty. The compressor shall be covered for an additional 3 years (parts only), for a total of 5 years from the date of installation.

WARRANTY CONDITIONS

1. Warranty labor must be performed by the local authorized service agent.
2. The equipment has been installed and operated in compliance with instructions provided.
3. Malfunctions or damage due to alterations, improper operation, outdoor use, neglect, vandalism, fire, acts of God, or any situation beyond the control of Aldevra are expressly excluded from this warranty.
4. Aldevra reserves the right to require that any parts covered under this warranty be returned to address provided prepaid and verified as defective upon examination by Aldevra.
5. Any damages resulting from shipment of the unit are expressly excluded. Aldevra advises customers to carefully examine all shipments prior to acceptance and note all potential damage concerns on the appropriate shipping papers.

Questions concerning this warranty should be directed to Aldevra at (269) 350-1337.

Return Goods Policy.

Return Policy for Follett Equipment Purchased Through GSA Schedule

Equipment may be returned for credit under the following conditions:

1. The equipment is new and unused.
2. A return authorization number has been issued by Aldevra customer service within 45 days after shipment.
3. Aldevra receives the equipment at the factory in Easton, PA within 30 days after issuance of the return authorization number.
4. The equipment is returned in original packaging. If the packaging has been damaged or discarded, Aldevra will forward new packaging at the customer's expense.

Note: Return freight charges are the responsibility of the customer. If equipment is returned and is damaged because of improper packaging, Aldevra will not be held responsible. Credit will be issued when the equipment has been inspected and deemed suitable to be returned to stock.

Note: A 20% restocking charge will be deducted from the credit. If the cost to return the product to stock exceeds the restocking fee, the actual cost will be deducted.

If Aldevra ships equipment not specified in contract to customer, Aldevra requests customer return in original packaging and Aldevra will pay for the item(s) to be returned if it was in error.

16. Export packing charges, if applicable. N/A
17. Terms and conditions of Government purchase card acceptance (any thresholds above the micro-purchase level). Accept
18. Terms and conditions of rental, maintenance, and repair (if applicable). N/A
19. Terms and conditions of installation (if applicable). Call for quote.
20. Terms and conditions of repair parts indicating date of parts price lists and any discounts from list prices (if applicable). N/A
- 20a. Terms and conditions for any other services (if applicable) N/A
21. List of service and distribution points (if applicable). N/A
22. List of participating dealers (if applicable). N/A
23. Preventive maintenance (if applicable). N/A
- 24a. Special attributes such as environmental attributes (e.g., recycled content, energy efficiency, and/or reduced pollutants). attached
- 24b. If applicable, indicate that Section 508 compliance information is available on Electronic and Information Technology (EIT) supplies and services and show where full details can be found (e.g. contractor's website or other location.) The EIT standards can be found at: www.Section508.gov/. N/A
25. Data Universal Number System (DUNS) number. 830063496
26. Notification regarding registration in Central Contractor Registration (CCR) database. Yes

